

8CH 8K LumiSearch NVR – 8 Port

R52-8PA



Key Features

- 8K NVR
- 8 Channels With Two (2) SATA Ports
- 8 PoE Ports With LumiPower Support
- HDMI/VGA Output
- Supports LumiSearch and LumiSearch+
- iMD, Face Recognition, and VCA by Recorder

Certifications and Compliance

- NDAA Compliant
- FCC

Learn More



Learn more about this product's key technologies.

Overview

The R52-8PA is part of Luminys's R5 series. R5 series devices are designed with a suite of advanced LumiTechnologies to meet the needs of today's evolving security market.

Key Technologies

LumiSearch

LumiSearch lets you quickly find, track, and identify targets in security footage using a reference image. The LumiSearch algorithm analyzes human body shape, clothing color, and other characteristics to accurately pinpoint where a target has appeared in footage captured by any LumiSearch-enabled camera and NVR. All R5 series NVRs support LumiSearch and LumiSearch+.

LumiPower

LumiPower technology enables long-distance Power over Ethernet transmission, extending power and data delivery up to 3,000 feet. This simplifies installations in larger or more complex environments by eliminating the need for additional power sources or repeaters. LumiPower ensures consistent connectivity and dependable power management, ideal for expansive security infrastructures.

LumiViewer

LumiViewer is a desktop and mobile application that streamlines security management by providing real-time surveillance, playback of historical footage, and instant alarm notifications. With features like device sharing, an alarm hub for safety alerts, visual intercom for video calls and door control, and remote access management, LumiViewer ensures comprehensive and efficient monitoring.

Specifications

Video

Video Input	8 Channels
Recording Resolutions	32MP, 16MP, 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 720p, D1, VGA, CIF
Output Resolutions	HDMI: 4K (3840 × 2160), 1920 × 1080, 1280 × 1024 VGA: 1920 × 1080, 1280 × 1024
Live View/Playback Resolutions	32MP, 16MP, 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 720p, D1, VGA, CIF

Decoding

Format	H.265, H.264, H.264H, H.264B, MJPEG
Capability	<p>AI On</p> <ul style="list-style-type: none"> 1CH at 32MP (30 fps) 2CH at 16MP (30 fps) 4CH at 8MP (30 fps) 8CH at 4MP (30 fps) <p>AI Off</p> <ul style="list-style-type: none"> 1CH at 32MP (30 fps) 3CH at 16MP (30 fps) 6CH at 8MP (30 fps) 12CH at 4MP (30 fps)
Live View Window Division	1, 4, 8, 9 Views
Auxiliary Port Window Division	1, 4, 8, 9 Views
Synchronous Playback	8 Channels

Supported Analytics

Intelligent Motion Detection	Camera: 8CH NVR: 8CH
Video Content Analytics (VCA)	Camera: 8CH NVR: 4CH 10 Rules per Channel
Face Recognition	<p>Face Capture and Recognition: 2CH Face Picture Comparison Alarm From Camera: 8CH</p> <p>Up to 20 Face Picture Libraries (Max. 20,000 Pictures Total)</p>
LumiSearch	8CH (Must be Supported by Camera)
Video Metadata	8CH (Analytics by Camera)
License Plate Recognition	<p>8CH (LPR Camera Required)</p> <p>Two (2) Block List, Two (2) Allow List</p> <p>Up to 20,000 Plate Numbers</p>

Interface

SATA	Two (2) Ports
HDD	Up to 16TB per HDD
Network	One (1) RJ-45 Self-Adaptive Ethernet (10/100/1000 Mbps)
PoE	Eight (8) RJ-45 Self-Adaptive Ethernet (10/100 Mbps)
USB	<p>Front Panel: 1 x USB 2.0</p> <p>Rear Panel: 1 x USB 3.0</p>
Serial Port	1 x RS-232
Alarm	<p>Input: Four (4) Channels</p> <p>Output: Two (2) Channels</p>
Audio	<p>Input: 1-Channel RCA Input</p> <p>Output: 1-Channel RCA Output</p>

Network

Bandwidth	<p>AI On</p> <ul style="list-style-type: none"> Incoming: 200 Mbps Outgoing: 200 Mbps <p>AI Off</p> <ul style="list-style-type: none"> Incoming: 256 Mbps Outgoing: 256 Mbps
Protocol	HTTP, HTTPS, TCP/IP, IPv4, IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS
Interoperability	ONVIF, RTSP
PoE Standard	IEEE 802.3 af/at
Client	LumiViewer, LumiViewer Mobile App

Electrical

Power Supply	100-240 V, 47-63 Hz
Power Consumption	<p>< 10 W (HDD Not Included)</p> <p>PoE: 130 W (Max. Output for Single Port: 25.5 W)</p>

Construction

Installation Method	Rack- or Desktop-Mount
Weight	2.6 kg (5.9 lb) Without HDD
Operating Temperature	−10 °C to 55 °C (14 °F to 131 °F) 10% to 93%
Dimensions (W × L × H)	372.0 × 325.8 × 43.7 mm (14.7 × 12.8 × 1.7 in.)

Certifications and Compliance

Certifications	FCC
Compliance	NDAA

Dimensional Drawing

mm [in.]

