

VertiLine33TD — Rack Mount DC Power Supply

Description

Altronix Vertiline33TD Rack Mount DC Power Supply provides sixteen (16) filtered and electronically regulated auto-resettable power outputs in a space saving 1U EIA 19" rack mount chassis.

| - Specifications | | | |
|------------------|--|---|--------------------------------|
| Input | Agency Listings | | |
| Voltage | 115VAC, 60Hz, 3A. | CE European Confo | rmity. |
| Output | | Physical and Environr | nental |
| Voltage | 12VDC. | Dimensions (H x W x D) | |
| Current | 16A max. total supply currect. | 1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm). | |
| Fusing | Individual outputs' PTCs rated @ 2.5A. | Product Weight 7.95 lbs. (3.61 kg). | |
| Other | Short circuit and thermal overload protection. Filtered and regulated. | Shipping Weight 9.05 lbs. (4.11 kg). | |
| | | Temperature | |
| | | Operating | 0°C to 49°C (32°F to 120°F). |
| Indicators (LED) | | Storage | -20°C to 70°C (-4°F to 158°F). |
| Master | Illuminated master power disconnect | Relative Humidity | 85% +/-5%. |
| Output | circuit breaker with manual reset. Sixteen (16) individual LEDs. | BTU/Hr. (approx.): | 98 BTU/Hr. |

VertiLine33TD



Rev. VertiLine33TD-05232017