

VertiLine63D Rack Mount DC Power Supply

Description

Altronix Vertiline63D Rack Mount DC Power Supply provides sixteen (16) filtered and electronically regulated auto-resettable power outputs in a space saving 1U EIA 19" rack mount chassis.

- Specifications				
Input		Agency Listings		
Voltage	115VAC, 60Hz, 3A.	CE European Confo	rmity.	
Output		Physical and Environmental		
Voltage	24VDC.	Dimensions (H x W x D)		
Current	8A max. total supply currect.	1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm).		
Fusing	Individual outputs' PTCs rated @ 2.5A.	Product Weight 7.2 lbs. (3.27 kg).		
Other	Short circuit and thermal overload protection. Filtered and regulated.	Shipping Weight 8.3 lbs. (3.76 kg).		
		Temperature		
		Operating	0°C to 49°C (32°F to 120°F).	
Indicators (LED)		Storage	-20°C to 70°C (-4°F to 158°F).	
Master	Illuminated master power disconnect	Relative Humidity	85% +/-5%.	
	circuit breaker with manual reset.	BTU/Hr. (approx.):	98 BTU/Hr.	
Output	Sixteen (16) individual LEDs.			

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA ______ phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

VertiLine63D

Altronix[®]

Rev. VertiLine63D-05242017